

GLASSOS® NANO WHITE Architectural Specifications 2017

Product Description - GLASSOS® Nano White is a superior quartz based surface material made from a proprietary blend of quartz powder and other fine minerals. GLASSOS® Nano White is a solid body material and it is fused together using only intense high temperature. No resins or petroleum glues are used in the process. The result is a pure white surface that is extremely hard, scratch resistant, UV stable, resistance to acid and alkali as well as bacteria resistant, free of radon and has absolutely no porosity.

Sizes and availability - Slabs are produced in nominal dimensions of 64" x 120" . Thicknesses include 1-1/4" , 3/4" and 7/16". Tiles are produced in 12x12, 18x18, 12x24, 24x24 all in 1/2" thickness. Cut to size tolerances on dimension are +/- 1/16" on slab and +/- 1/32 on tile. The back of the slabs may have some irregularities from the manufacturing process. Calibration may be required to get a uniform thickness on the edge.

Applications – Walls, floors, counter tops, vanity tops, shower jambs, sills, niches, saddles and exterior panels.

Suggested Minimum Joint Width and allowances – Interior horizontal countertop seams up to 25" deep require a joint space of 1/32" min, 1/16" -1/8" joint when greater than 25" deep. Interior vertical panels up to 25" minimum require a joint space of 1/16" – 1/8", 1/8" -1/4" when greater than 25" deep. Suggested minimum exterior joint width 7/16". There must be a minimum 4" set back for all sink and cook top cut outs. All inside corners including sink cut outs, cook top cut outs, outlets, bump outs and notches must have a minimum 1/2" inside radius corner.

Satin Texture – GLASSOS® Nano is stocked in a polished finish and available in GLASSOS® Satin Texture. Satin Texture is a matte finish that removes the polish and increases the coefficient of friction on GLASSOS® products. The treatment is available on tile, cut to size projects and full size slabs.

Installation – For seams and mitered laminations on GLASSOS® Nano White our craftsmen use GLASSOS® Nano Bond cartridges. Counter tops and other interior horizontal surfaces may be installed using Silicone® adhesive. Vertical surfaces may be installed using White Portland Cement such as Laticrete® Platinum or Latapoxy® for exterior and wet areas.

Care and Maintenance – No sealer required. Will never yellow or stain. Clean with a soft cloth or paper towel using glass cleaner . **Don't use abrasive household surface cleaners or abrasive sponges. Avoid placing heavy or abrasive objects on the surface without adequate protection. Always use a cutting board.**

<u>Test</u>	<u>Results</u>	<u>Test Method</u>	
MOHS Hardness	7	MOHS scratch hardness	
Water Absorption	.04	ASTM C373	
Resistance to Chemicals	Class B rating	ASTM C650	
Abrasion Resistance	Class 3 rating	ASTM C1027	
Crazing Resistance	No evidence of Crazing	ASTM C424	
Static Coefficient of Friction	Wet .44, Dry .75	ASTM C1028	Polished surface
Static Coefficient of Friction	Wet .79, Dry .87	ASTM C1028-07	Satin Texture surface

Test details available upon request.

GLASSOS® is a registered trademark of:



CCS STONE, Inc,
9-11 Caesar Place
Moonachie, NJ 07074

info@ccsstone.com

www.ccsstone.com

201-933-1515 800-227-7785 fax 201-933-5744

