

GLASSOS® NANO WHITE

SPEC SHEET



Product Description - Made from quartz powder and a proprietary blend of minerals, GLASSOS ® Nano White is fused together using only intense high temperature exceeding 3000 f. No resins or petroleum glues are used in the process. The result is a pure white surface that is extremely hard, scratch resistant and has absolutely no porosity.

Sizes and availability - Tiles are stocked in 12x12, 12x24, 24x24 and 24x36x7/16” thickness. Slabs are 120x56 x 3/4” and 1-1/4” and 120x47 x 7/16” Available cut to size, special shapes and sizes. Tile and slab thickness is nominal with tolerances 1/16 + /-.

Applications – Walls, floors, counter tops, vanity tops, shower jambs, sills and exterior panels

Care and Maintenance – Requires no sealer ever. Will never yellow or stain. Clean with a soft cloth using glass cleaner or ph neutral soap and water.

Finishes – Available from stock in polished or satin Texture finish.

Test	Results	Test Method
Mohs Hardness	7	MOHS Scratch Hardness
Water Absorption	.04	ASTM C373
Resistance to Chemicals	Class B rating	ASTM C650
Abrasion Resistance	Class 3 rating	ASTM C1027
Crazing Resistance	no evidence of crazing	ASTM C424
Static Coefficient of Friction	Wet .44, Dry .75	ASTM C1028

Test details available upon request.

Sold exclusively through:



CCS STONE, Inc.
9-11 Caesar Place
Moonachie, NJ 07074

T 201-933-1515
F 201-933-5744
www.ccsstone.com